



ANABEC
SOLUTIONS

Choose the **ANABEC SOLUTIONS** | Better Chemistry. Superior Results.



NEWBUILD 50

Scientifically Proven - Environmentally Friendly

*Restrictions Apply

NEW BUILD 50 is a water based acrylic moisture barrier that can be applied to CPVC, Romes, Galvanized metal, PEX, Engineered lumber, Fire treated lumber and metal fasteners without negative results or any off gassing. The active microbial fighting ingredient is silver nitrate.

BENEFITS

- Liability protection for 50 years
- Adds value to home or commercial buildings
- Provides peace of mind to owner
- Offers increased sellability

APPLICATION

- Designed for all unfinished building surfaces
- Available in clear, white and blue
- Serves as an excellent primer for latex paints
- Covers 1,000 sq. ft per gallon
- The best coverage in the industry!

ADCOinnovations inc.

Mold Prevention & Remediation ■ Advanced Building Products

Serving the Mid-Atlantic Region

410-394-MOLD (6653)

www.adcoinnovations.com

2970 Saint Leonard Road
Port Republic, MD 20676



Southwire
ROMEX

CHARLOTTE
PIPE AND FOUNDRY COMPANY

uponor
PEX PIPING



ASTM D3273-16

Lubrizol

It is Highly Recommended that Anabec Products be applied "PRIOR" to any mechanical installations in New Construction.

NewBuild 50 is approved by:



"FBC™ System Compatible indicates that this product has been tested, and is monitored on an ongoing basis, to assure its chemical compatibility with FlowGuard Gold®, BlazeMaster® and Corzan® piping systems and products made with TempRite® Technology." "The FBC System Compatible Logo, FBC™, FlowGuard Gold®, BlazeMaster®, Corzan®, and TempRite® are trademarks of Lubrizol Advanced Materials, Inc. or its affiliates."

NEWBUILD 50

Phone: 410-394-6653 | www.adcoinnovations.com

Anabec Solutions

Classification: Moisture Barrier
Key Ingredient(s): Acrylic
Silver

NEWBUILD 50

Scientifically Proven - Environmentally Friendly

Packaging

Packaged	5 gal Bucket
Color as Packed	Clear Opaque White Opaque Blue
Shelf Life	18 months
Storage Conditions	Do not Freeze Store out of reach of children

Properties

Finish after applied	Clear Sheen Translucent White Translucent Blue
Odor	None
pH	6.4- 9.0
Viscosity	700 - 900 cps
Density	8.33 lbs/gal
Flash Point	>100 C
Est VOC	0.71 lbs/gal
Solubility in Water	Soluble

Application

Dilution	Ready to use
Coverage	800-1000 sq ft/gal
Air Less Sprayer	Yes
Brush	Yes
Roller	Yes
Reoccupy space	30 mins
Dry to Touch	2 hours
Dry Through	18-24 hours
Clean up	Soap and Water



Choose the **ANABEC SOLUTIONS**
Better Chemistry. Superior Results.

ADCO*innovations* inc.

Mold Prevention & Remediation ■ Advanced Building Products

Serving the Mid-Atlantic Region

410-394-MOLD (6653)
www.adcoinnovations.com
2970 Saint Leonard Road
Port Republic, MD 20676