

ADCO *innovations* inc.

Mold Prevention & Remediation ■ Advanced Building Products

Serving the Mid-Atlantic Region

410-394-MOLD (6653)

www.adcoinnovations.com

x90

x90 is a second step in the Anabec System of Products. Application of x90 results in an extremely durable moisture barrier. x90 is applied after cleaning the surface with Advanced Cleaning Solution. This product is appropriate for use on previously cleaned and/or disinfected, unfinished building material surfaces. x90 can serve as a primer for latex paints.

x90

General Characteristics:

- Ready to Use
- Surface Penetrant

Color:

- Solid White

Coverage:

- 250-400 sq ft / gallon

Choose the **Anabec System** Better Chemistry. Superior Results.

x90

Product Info

Classification
Key Ingredient(s)

Moisture Barrier
Latex
Silver

Packaging / Storage

Packaged	5 gal
Shelf Life	18 months
Storage Conditions	Do not Freeze Store out of reach of children

Properties

Finish after applied	Opaque White
Odor	Solvent / Latex
pH	7-9
Viscosity	4,000-10,000 cps
Density	10.2 lbs/gal
Flash Point	>100 C
Est VOC	0.15
Solubility in Water	Soluble

Application

Dilution	Ready to Use
Coverage	250-400 sq ft
Air Less Sprayer	Yes
Foggable	No
Brush	Yes
Roller	Yes
Dry to touch	2 hours
Dry through	18-24 hours
Clean-up	Water / Soap



ADCO *innovations* inc.

Mold Prevention & Remediation ■ Advanced Building Products

Serving the Mid-Atlantic Region

410-394-MOLD (6653)
www.adcoinnovations.com

13325 Rousby Hall Rd.
Lusby, MD 20657